



PES 30

General Purpose Degreaser and Tank Cleaner

PRODUCT DESCRIPTION

A heavy duty solvent emulsifier economical and ready to use, containing petroleum solvents, emulsifiers and surfactants, used as a tank cleaner or for general degreasing.

DIRECTIONS FOR USE AND DOSE RATES

* PES 30 is recommended for local cleaning and degreasing and conventional means. Apply undiluted over soiled area and allow a contact time of between 15-30 minutes before rinsing off with water.

** SOAK METHOD:*

Put parts to be cleaned into a bath of PES 30 undiluted for heavy soil, for medium to light soiling use a solution of between 10-30% PES 30 in water. Parts should be soaked for at least 30 minutes before washing off with water.

** SPRAY METHOD:*

Spray PES 30 undiluted over all soiled areas. Allow time for PES 30 to act, between 15-30 minutes, then rinse off by water hose. For stubborn deposits, agitation by scrubbing will assist the cleaning operation.

IN SERVICE CLEANING:

This method may be undertaken with engine running at normal speed.

FEATURES AND BENEFITS

- * Wide application range - from tank cleaning to heavy duty degreasing.
- * Wide cleaning spectrum - effective on mineral oils and petroleum based chemicals.
- * Powerful solvent with quick penetration and emulsifying properties.
- * Rapid rinsing, leaving clean oil-free surfaces.
- * Safe to use on most metal surfaces, painted surfaces and tank linings.
- * Recommended for use with high pressure and steam cleaning equipment.

APPLICATIONS

- * Cargo tank cleaning of mineral oils and petroleum based chemicals.
- * Cleaning oil coolers, fuel oil preheaters, lube oil heat exchangers.
- * Cleaning and degreasing of cooling water systems prior to descaling operations.
- * Degreasing double bottom, deep tanks and bilges etc.
- * Removal of general oil contamination from machinery and engine room.
- * Cleaning/degreasing of boilers.
- * Soak cleaning of machinery parts.