



Fishers Way, Belvedere, Kent. DA17 6BS.  
Tel: 0870 7700530 Fax: 0870 7700531  
Email: Sales@Performance-Chemicals.net



Registered in England No. 568338  
Registered Office:  
21 Station Road West  
Oxted, Surrey RH8 9EC  
VAT No. GB 219 4484 49

## **PERFORMANCE SUPERWASH**

SUPERWASH is a non-caustic, non hazardous liquid blend of surfactants, alkali and solvent in concentrated form. The product is a powerful, biodegradable, degreaser removing soil from hard surfaces. Suitable for both domestic and industrial use.

### **APPLICATIONS**

SUPERWASH can be used in a variety of applications to remove grease, grime and traffic film from walls, floors, paintwork, plastic, machinery, equipment, engines, lorry and tanker bodies, railway/underground rolling stock etc. Superwash is suitable for use in pressure washers, steam cleaners and foaming equipment in applications where some foam or a stable foam is desirable.

### **USAGE INSTRUCTIONS**

For walls floors and paintwork use Superwash at a dilution of between 1 and 2% in water. Apply by spray, brush or sponge.

For machinery and vehicle bodies use superwash at a dilution between 1 and 2% in water. Apply by spray, brush or sponge.

For pressure washing and steam cleaning use in the detergent tank at a dilution of between 1 and 2% in water.

In all applications higher concentrations may be required depending on the degree of soiling. After use rinse off with clean water.

**PACKAGING:** 25 litre drums

NB At dilutions of 11% or less the pH of a solution of Superwash will be below 11.

SUPERWASH is also available with added active ingredients to enhance surface sheen after use.

If interested please ask for **SUPERWASH PLUS**.